





















INTRODUCTION

The All-in-One solar LED street light is the newest technology for solar street lights. With its all-in-one design, its solar panel, LED lamp, lithium battery and charging controller are all integrated into one single body. With this new technology, there is no need for cables or any digging of underground spaces to store its battery. Installation can also be done very quickly. Additionally, this solar LED street light is comprised of the latest intelligent lighting system. The lamp works automatically based on day and night. It has three settings including a motion sensor, time schedule and internet control. to meet different requirements. There will be no need for unnecessary settings after installation. Compared to traditional solar street lights, it is much easier to install and transport, with a longer lifespan than lead-acid batteries and is also cheaper to maintain.



PRODUCT STRUCTURE



PRODUCT PICTURE





DATA SHEET

LIG	1 H	N	G
	-	 _	

Efficiency	200-240LM/W		
LED Chip	Philips 3030 (certified per IESNA LM-80 TM-21)		
CCT	3000-6000K		
Life span	50 000 hours (12 years)		
Max power	160W		
Nominal pov	wer 80W		
Typical Lum Flux	uminous 16000-19200LM		
Beam angle	80°x150°		
Working wa	y Motion Sensor/Time Schedule		

PHOTOVOLTAIC PANEL

Technology	Mono-crystalline photovoltaic panels	
Power of PV Module	180Wp	
Lifespan	25 years	

BATTERY

Technology	LiFePO4(Lithium Iron Phosphate)		
Lithium Battery	1076WH		
Autonomy	3-5 Rainy days		
Lifespan	12 years		

CHARGING CONTROLLER

Technology	MPPT(Maximum Power Point Tracking)
Lifespan	12 years

GENERAL

Dimensions	1697*587*165MM	
Weight	29.6KG	
IP	IP66	
Working Temperature	-20°C~+60°C	
Recommended Installation Height	10-12 M	
Recommended Installation Distance	45-50M	
Recommended Diameter of Top mounting	75-80MM	

LUX DATA

