

INTRODUCTION

The All-in-One solar LED street light is the newest technology for solar street lights. With its all-in-one design, its solar panel, LED lamp, lithium battery and charging controller are all integrated into one single body. With this new technology, there is no need for cables or any digging of underground spaces to store its battery. Installation can also be done very quickly. Additionally, this solar LED street light is comprised of the latest intelligent lighting system. The lamp works automatically based on day and night. It has three settings including a motion sensor, time schedule and internet control, to meet different requirements. There will be no need for unnecessary settings after installation. Compared to traditional solar street lights, it is much easier to install and transport, with a longer lifespan than lead-acid batteries and is also cheaper to maintain.



PRODUCT STRUCTURE



PRODUCT PICTURE





DATA SHEET

	LIGHT	ING
Efficiency	20	0-240LM/W
LED Chip	Philips 3030 (certif	ied per IESNA LM-80 TM-21)
ССТ	3C	000-6000K
Life span	50 000	hours (12 years)
Max power		60W
Nominal por	ver	30W
Typical Lum Flux	nous 60	00-7200LM
Beam angle		80°x150°
Working wa	y Motion Se	nsor/Time Schedule

PHOTOVOLTAIC PANEL

Technology	Mono-crystalline photovoltaic panels		
Power of PV Module	9 70Wp		
Lifespan	25 years		

RATTERY

Technology	LiFePO4(Lithium Iron Phosphate)	
Lithium Battery	384WH	
Autonomy	3-5 Rainy days	
Lifespan	12 years	

CHARGING CONTROLLER

Technology	MPPT(Maximum Power Point Tracking)
Lifespan	12 years

GENERAL

Dimensions	1037*407*150MM	
Weight	13.1KG	
IP	IP66	
Working Temperature	-20°C~+60°C	
Recommended Installation Height	5-7M	
Recommended Installation Distance	20-25M	
Recommended Diameter of	55-60MM	

LUX DATA

